


Tube No.
120SF

HYDROGEN SULPHIDE




1. PERFORMANCE

- | | | | |
|--------------------------|---|--------------|------------|
| 1) Measuring range | : 100-2,000 ppm | 50-1,000 ppm | 25-500 ppm |
| Number of pump strokes | 1/2 (50mL) | 1 (100mL) | 2 (100mL) |
| 2) Sampling time | : 1 minute/1 pump stroke | | |
| 3) Detectable limit | : 0.5 ppm (100mL) | | |
| 4) Shelf life | : 3 years | | |
| 5) Operating temperature | : 0~40°C | | |
| 6) Reading | : Direct reading from the scale calibrated by 1 pump stroke | | |
| 7) Colour change | : White→Black | | |

2. RELATIVE STANDARD DEVIATION

RSD-low : 10% RSD-mid. : 10% RSD-high : 10%

3. CHEMICAL REACTION



4. CALIBRATION OF THE TUBE

STANDARD GAS CYLINDER METHOD

5. INTERFERENCE AND CROSS SENSITIVITY

(NOTE)

In case of 1/2 pump strokes, following formula is available for the actual concentration.

Actual concentration = 2 × Reading value

In case of 2 pump strokes, following formula is available for the actual concentration.

Actual concentration = 1/2 × Reading value