



## 1. PERFORMANCE


- 1) Measuring range : 0.05-1.0%  
Number of pump strokes : 1 (100mL)
- 2) Sampling time : 5 minutes/1 pump stroke
- 3) Detectable limit : 50 ppm
- 4) Shelf life : 2 years
- 5) Operating temperature : 0 ~ 40 °C
- 6) Temperature compensation : Necessary (See "TEMPERATURE CORRECTION TABLE")
- 7) Reading : Direct reading from the scale calibrated by 1 pump stroke
- 8) Colour change : Purple blue → Pale pink

## 2. RELATIVE STANDARD DEVIATION

RSD-low : 10% RSD-mid. : 5% RSD-high : 5%

## 3. CHEMICAL REACTION

By reacting with alkali, PH indicator is discoloured.



## 4. CALIBRATION OF THE TUBE

STANDARD GAS CYLINDER METHOD

## 5. INTERFERENCE AND CROSS SENSITIVITY

Substance	Interference	ppm	Coexistence
Chlorine	The accuracy of readings is not affected.		The accuracy of readings is not affected.
Hydrogen sulphide	"		"
Nitrogen dioxide	"		"
Sulphur dioxide	"		"
Hydrogen cyanide	Similar stain is produced.	120	Higher readings are given.

TEMPERATURE CORRECTION TABLE

Tube Readings (%)	Corrected Concentration (%)				
	0°C (32°F)	10°C (50°F)	20°C (68°F)	30°C (86°F)	40°C (104°F)
1.0	1.16	1.09	1.00	0.94	0.89
0.9	1.05	0.98	0.90	0.85	0.80
0.8	0.93	0.87	0.80	0.75	0.70
0.7	0.81	0.76	0.70	0.66	0.62
0.6	0.70	0.65	0.60	0.57	0.53
0.5	0.58	0.54	0.50	0.47	0.44
0.4	0.46	0.43	0.40	0.38	0.35
0.3	0.36	0.33	0.30	0.28	0.26
0.2	0.24	0.22	0.20	0.19	0.17
0.1	0.12	0.11	0.10	0.09	0.08